

Program LEQ Professional v. 6-2016 dla Windows

Projekt:

Z:\Amanowicz\05.09.2018\III etap\dzień 4 m.dat

Dane do obliczeń :

Współczynnik gruntu (całego obszaru analizy)-global G = 0.000

Temperatura otoczenia 10[°C]

•różnica punktowe

Nr	X[m]	Y[m]	z[m]	Pma	Symbol
1	491.8	583.0	4.6	82.0	B5E1
2	486.0	564.0	4.6	82.0	B5E2
3	479.0	545.6	4.6	82.0	B5E3
4	474.8	535.8	1.6	89.4	B5E4
5	471.6	590.0	4.6	82.0	B6E1
6	465.6	571.0	4.6	82.0	B6E2
7	459.2	552.0	4.6	82.0	B6E3
8	455.4	542.4	1.6	89.7	B6E4
9	454.6	595.4	4.6	82.0	B7E1
10	448.6	577.0	4.6	82.0	B7E2
11	442.0	557.6	4.6	82.0	B7E3
12	438.8	548.0	1.6	89.4	B7E4
13	437.6	601.6	4.6	82.0	B8E1
14	430.6	582.6	4.6	82.0	B8E2
15	424.8	563.2	4.6	82.0	B8E3
16	421.6	553.2	1.6	89.4	B8E4
17	417.2	608.0	4.6	82.0	B9E1
18	410.8	588.6	4.6	82.0	B9E2
19	404.6	569.4	4.6	82.0	B9E3
20	400.6	560.4	1.6	89.4	B9E4
21	568.4	606.6	5.5	81.9	B10E1
22	518.8	571.2	2.3	96.4	A1
23	602.0	596.0	0.5	72.2	A1a
24	585.0	600.0	0.5	72.2	A1b
25	108.0	732.0	0.5	69.2	A2a
26	278.0	677.0	0.5	69.2	A2b
27	467.0	701.0	0.5	69.2	A2c
28	582.0	663.0	0.5	69.2	A2d
29	556.0	619.0	0.5	69.2	A2e
30	551.0	602.0	0.5	69.2	A2f
31	568.0	626.0	0.5	69.2	A2g
32	565.0	616.0	0.5	69.2	A2h
33	392.0	548.0	0.5	69.2	A4a
34	413.3	540.8	0.5	69.2	A4b
35	434.5	533.5	0.5	69.2	A4c
36	455.8	526.3	0.5	69.2	A4d
37	477.0	519.0	0.5	69.2	A4e
38	111.0	731.0	0.5	69.2	A5a
39	229.0	695.0	0.5	69.2	A5b
40	338.0	565.0	0.5	75.2	A6a
41	130.0	632.0	0.5	75.2	A6b

42	583.0	574.0	0.5	71.2	A7a
43	552.0	584.0	0.5	71.2	A7b
44	395.9	618.6	0.5	71.2	B13E1
45	390.6	607.4	0.5	71.2	B13E2
46	389.8	596.5	0.5	71.2	B13E3
47	383.0	584.7	0.5	71.2	B13E4
48	381.1	573.2	0.5	71.2	B13E5
49	378.3	568.5	0.5	71.2	B13E6
50	371.6	626.4	0.5	71.2	B14E1
51	365.1	615.5	0.5	71.2	B14E2
52	364.3	603.8	0.5	71.2	B14E3
53	358.1	593.4	0.5	71.2	B14E4
54	356.7	580.5	0.5	71.2	B14E5
55	356.4	574.4	0.5	71.2	B14E6
56	346.4	635.1	0.5	71.2	B15E1
57	341.3	623.4	0.5	71.2	B15E2
58	340.2	611.0	0.5	71.2	B15E3
59	334.9	601.0	0.5	71.2	B15E4
60	332.4	588.6	0.5	71.2	B15E5
61	333.2	582.2	0.5	71.2	B15E6
62	322.6	642.4	0.5	71.2	B16E1
63	316.7	631.2	0.5	71.2	B16E2
64	314.2	620.0	0.5	71.2	B16E3
65	308.6	608.2	0.5	71.2	B16E4
66	308.3	596.2	0.5	71.2	B16E5
67	307.4	590.6	0.5	71.2	B16E6
68	296.8	650.5	0.5	71.2	B17E1
69	291.8	638.5	0.5	71.2	B17E2
70	289.5	626.7	0.5	71.2	B17E3
71	284.2	616.4	0.5	71.2	B17E4
72	282.5	604.0	0.5	71.2	B17E5
73	282.5	598.2	0.5	71.2	B17E6
74	375.0	554.0	0.5	69.2	A4f
75	349.8	562.0	0.5	69.2	A4g
76	324.5	570.0	0.5	69.2	A4h
77	299.3	578.0	0.5	69.2	A4i
78	274.0	586.0	0.5	69.2	A4j
79	360.1	715.9	5.6	82.0	B1E1
80	368.5	710.3	5.6	82.0	B1E2
81	378.6	709.4	5.6	82.0	B1E3
82	385.8	704.7	5.6	82.0	B1E4
83	396.5	704.1	5.6	82.0	B1E5
84	404.0	698.8	5.6	82.0	B1E6
85	415.0	698.5	5.6	82.0	B1E7
86	421.7	693.2	5.6	82.0	B1E8
87	431.8	693.5	5.6	82.0	B1E9
88	440.7	691.2	5.5	80.9	B1E10
89	439.9	686.8	5.5	80.9	B1E11
90	447.7	688.2	5.5	80.9	B1E12
91	447.4	684.8	5.5	80.9	B1E13
92	456.7	685.4	5.5	80.9	B1E14
93	455.3	680.9	5.5	76.9	B1E15
94	462.8	680.9	5.6	82.0	B2E1
95	472.9	679.8	5.6	82.0	B2E2
96	481.0	675.3	5.6	82.0	B2E3
97	490.3	673.9	5.6	82.0	B2E4

98	498.4	669.4	5.6	82.0	B2E5
99	508.5	666.0	5.6	82.0	B2E6
100	517.7	665.8	5.6	82.0	B2E7
101	525.0	660.7	5.6	82.0	B2E8
102	535.6	659.6	5.6	82.0	B2E9
103	542.4	654.6	5.6	82.0	B2E10
104	552.2	655.1	5.6	82.0	B2E11
105	559.4	649.0	5.6	82.0	B2E12
106	569.8	649.0	5.6	82.0	B2E13
107	320.6	692.6	5.8	76.9	B3E1
108	315.6	677.0	5.8	76.9	B3E2
109	328.2	690.4	5.8	76.9	B3E3
110	323.1	674.7	5.8	81.9	B3E4
111	336.6	688.7	5.8	81.9	B3E5
112	330.7	671.9	5.8	81.9	B3E6
113	344.1	685.6	5.8	81.9	B3E7
114	338.2	669.1	5.8	81.9	B3E8
115	351.7	682.8	5.8	81.9	B3E9
116	346.4	666.6	5.8	81.9	B3E10
117	359.2	680.3	5.8	81.9	B3E11
118	353.9	665.2	5.8	81.9	B3E12
119	367.4	678.6	5.8	81.9	B3E13
120	361.5	661.8	5.8	81.9	B3E14
121	374.6	675.8	5.8	81.9	B3E15
122	369.6	659.0	5.8	81.9	B3E16
123	384.2	672.2	5.8	81.9	B3E17
124	379.1	656.8	5.8	81.9	B3E18
125	391.4	670.5	5.8	81.9	B3E19
126	386.7	654.6	5.8	81.9	B3E20
127	400.1	667.4	5.8	81.9	B3E21
128	394.0	651.8	5.8	81.9	B3E22
129	407.4	665.2	5.8	81.9	B3E23
130	402.1	649.2	5.8	81.9	B3E24
131	414.7	663.0	5.8	81.9	B3E25
132	409.9	647.0	5.8	81.9	B3E26
133	423.4	660.4	5.8	81.9	B3E27
134	417.2	644.2	5.8	81.9	B3E28
135	429.2	658.2	5.8	81.9	B3E29
136	425.0	642.0	5.8	81.9	B3E30
137	437.9	655.7	5.8	81.9	B3E31
138	432.9	639.2	5.8	81.9	B3E32
139	444.6	653.4	5.8	81.9	B3E33
140	440.2	637.8	5.8	81.9	B3E34
141	448.3	652.9	5.8	76.9	B3E35
142	454.4	649.8	5.8	76.9	B4E1
143	448.3	634.1	5.8	81.9	B4E2
144	460.3	648.1	5.8	81.9	B4E3
145	454.7	632.4	5.8	81.9	B4E4
146	468.2	646.2	5.8	81.9	B4E5
147	462.8	630.2	5.8	81.9	B4E6
148	477.4	642.5	5.8	81.9	B4E7
149	472.1	626.8	5.8	81.9	B4E8
150	486.4	640.3	5.8	81.9	B4E9
151	480.5	624.3	5.8	81.9	B4E10
152	494.5	637.5	5.8	81.9	B4E11
153	489.4	621.5	5.8	81.9	B4E12

154	503.7	635.5	5.8	81.9	B4E13
155	498.4	619.0	5.8	81.9	B4E14
156	512.1	631.9	5.8	81.9	B4E15
157	507.1	616.5	5.8	81.9	B4E16
158	520.8	628.8	5.8	81.9	B4E17
159	514.9	613.1	5.8	81.9	B4E18
160	530.3	625.7	5.8	81.9	B4E19
161	525.6	610.0	5.8	81.9	B4E20
162	538.4	623.2	5.8	81.9	B4E21
163	534.8	607.2	5.8	81.9	B4E22
164	231.0	690.0	0.5	72.2	A8a
165	213.0	682.0	0.5	72.2	A8b
166	187.0	675.4	-1.5	70.0	M1
167	179.0	666.8	3.3	87.0	M2
168	179.0	666.8	5.1	87.0	M3
169	179.0	666.8	7.2	89.0	M4
170	178.8	666.9	9.6	89.0	M5
171	178.8	667.1	12.0	89.0	M6
172	178.9	667.2	14.6	89.0	M7
173	179.0	675.5	5.0	80.0	M8
174	184.6	645.4	1.0	80.0	M9
175	183.5	646.9	2.0	80.0	M10
176	183.4	645.4	2.0	80.0	M11
177	174.3	662.6	25.0	60.0	M12
178	178.7	676.2	25.0	75.0	M17
179	178.0	668.3	25.0	75.0	M18
180	196.6	642.7	25.0	75.0	M19
181	273.3	703.9	1.0	85.0	S1
182	274.1	702.8	1.0	85.0	S2
183	272.7	698.0	1.0	79.0	P1

=====

•ród³a liniowe - wspó³rzêdne

Nr	X1[m]	Y1[m]	X2[m]	Y2[m]	z1[m]	z2[m]	Pma	Symbol
1	166.1	665.0	156.7	636.6	1.0	25.0	70.0	M13
2	166.2	664.7	175.4	661.6	1.0	25.0	70.0	M14
3	174.1	661.6	164.8	634.4	1.0	25.0	70.0	M15
4	165.9	637.0	179.9	647.2	1.0	25.0	70.0	M16
5	171.8	638.5	180.2	646.7	1.5	1.5	89.0	M20
6	167.8	644.6	179.7	647.2	1.5	1.5	89.0	M21
7	173.8	646.4	180.6	647.3	1.5	1.5	89.0	M22
8	170.5	652.2	180.5	648.1	1.5	1.5	89.0	M23
9	177.0	653.8	180.5	648.4	1.5	1.5	89.0	M24
10	173.8	659.5	180.5	647.7	1.5	1.5	89.0	M25
11	186.6	645.5	198.2	641.7	1.5	1.5	89.0	M26

=====

•ród³a typu hala produkcyjna :

WSPÓRZÊDNE WIERZCHOŃKÓW :

Nr	X1[m]	Y1[m]	X2[m]	Y2[m]	X3[m]	Y3[m]	X4[m]	Y4[m]	h0[m]	h[m]
1	488.6	594.9	501.9	590.6	482.8	534.1	469.2	538.0	0.0	4.8
2	467.7	602.8	480.3	597.4	462.0	540.2	449.7	544.2	0.0	4.8
3	451.5	606.8	464.1	602.5	445.0	546.7	433.9	549.9	0.0	4.8
4	432.4	612.9	447.2	609.0	428.1	550.6	415.5	554.2	0.0	4.8

5	412.3	619.4	426.3	615.4	408.3	558.2	393.6	562.2	0.0	4.8
6	560.2	613.6	575.7	608.6	572.8	600.0	557.7	605.0	0.0	5.0
7	388.1	627.0	405.7	622.2	387.2	564.6	370.4	570.2	0.0	4.7
8	362.6	634.6	380.2	629.8	362.6	572.7	345.8	579.1	0.0	4.7
9	338.8	643.0	356.2	637.4	338.8	580.5	321.4	586.1	0.0	4.7
10	313.3	651.9	330.4	646.3	313.9	588.6	295.7	593.4	0.0	4.7
11	289.0	659.2	306.3	653.9	288.4	595.9	272.2	602.1	0.0	4.7
12	352.0	705.9	360.1	727.2	463.4	692.8	455.3	670.9	0.0	5.3
13	464.0	693.9	578.2	658.6	570.1	635.1	455.6	671.2	0.0	5.3
14	318.4	702.3	450.5	660.8	441.0	627.8	309.4	670.9	0.0	6.5
15	454.7	659.7	546.0	630.0	536.8	598.4	440.4	628.9	0.0	6.5

POZIOMY HAŁASU i IZOLACYJNOŚĆ PRZEGRÓD

Nr Źródła		A	63	125	250	500	1000	2000	4000	8000	wsp. odb.
1	sc.1	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.2	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.3	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.4	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	dach	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R d	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

Nr Źródła		A	63	125	250	500	1000	2000	4000	8000	wsp. odb.
2	sc.1	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.2	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.3	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.4	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	dach	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R d	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

Nr Źródła		A	63	125	250	500	1000	2000	4000	8000	wsp. odb.
3	sc.1	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.2	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.3	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.4	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	dach	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R d	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

Nr Źródła		A	63	125	250	500	1000	2000	4000	8000	wsp. odb.
4	sc.1	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000

	R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
sc.2	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
sc.3	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
sc.4	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
dach	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R d	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

Nr Źródła		A	63	125	250	500	1000	2000	4000	8000	wsp. odb.
5	sc.1	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.2	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.3	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.4	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	dach	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R d	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

Nr Źródła		A	63	125	250	500	1000	2000	4000	8000	wsp. odb.
6	sc.1	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.2	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.3	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.4	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	dach	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R d	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

Nr Źródła		A	63	125	250	500	1000	2000	4000	8000	wsp. odb.
7	sc.1	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.2	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.3	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.4	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	dach	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R d	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

Nr Źródła		A	63	125	250	500	1000	2000	4000	8000	wsp. odb.
8	sc.1	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.2	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.3	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000

	R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
sc.4	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
dach	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R d	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

Nr Źródła		A	63	125	250	500	1000	2000	4000	8000	wsp. odb.
9	sc.1 L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.2 L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.3 L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.4 L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	dach L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R d	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

Nr Źródła		A	63	125	250	500	1000	2000	4000	8000	wsp. odb.
10	sc.1 L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.2 L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.3 L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.4 L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	dach L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R d	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

Nr Źródła		A	63	125	250	500	1000	2000	4000	8000	wsp. odb.
11	sc.1 L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.2 L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.3 L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.4 L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	dach L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R d	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

Nr Źródła		A	63	125	250	500	1000	2000	4000	8000	wsp. odb.
12	sc.1 L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.2 L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.3 L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.4 L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	dach L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000

		R d	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
=====												
Nr	Źródła	A	63	125	250	500	1000	2000	4000	8000	wsp.odb.	
=====												
13	sc.1	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.2	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.3	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.4	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	dach	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R d	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

=====												
Nr	Źródła	A	63	125	250	500	1000	2000	4000	8000	wsp.odb.	
=====												
14	sc.1	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.2	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.3	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.4	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	dach	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R d	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

=====												
Nr	Źródła	A	63	125	250	500	1000	2000	4000	8000	wsp.odb.	
=====												
15	sc.1	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.2	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.3	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.4	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	dach	L wew	85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R d	25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

Punkty obserwacji

Nr	Symbol	X[m]	Y[m]	z[m]
1		750.1	723.2	4.0
2		400.6	852.5	4.0
3		472.3	482.6	4.0
4		167.7	590.1	4.0
5		84.5	241.9	4.0
6		108.8	30.7	4.0